

PDF DATA SHEET EFORCEAUSTRALIA PTY.LTD ACN:159 503 401

AO-Z-473 /1~50uJ/1~500mW

SPECIFICATIONS

LD PUMPED ALL-SOLID-STATE AOM Q-SWITCHED LASER

All solid state AOM Q-switched laser at 473 nm has the features of high peak power, high repetition rate, and short pulse duration, which is widely used in marking, carving, measure, research and so on.



Wavelength (nm)	473±1	
Operating mode	Q-switch: AOM (Acousto-Optic Modulation)	
Output power(mW)	1~500	
Single pulse energy (µJ)	1~50	
Pulse duration (ns)	~230@10kHz	
Peak power (W)	~210	
Rep. rate (kHz)	1~50, adjustable by external control	
Ave power stability (over 4 hours)	<5%, <10%	
Warm-up time (minutes)	<10	
Beam divergence, full angle (mrad)	<2	
Beam diameter at the aperture (mm)	~4.0	
Beam height from base plate (mm)	96	
Cooled method	Air cooled	
Operating temperature (°C)	10~35	
Power supply (220/110VAC)	PSU-AOM(3U)	
Expected lifetime (hours)	10000	
Warranty period	1 year	





AO-Z-473	Dimensions	PSU-AOM(3U)	Dimensions
440(L)×114(W) ×130(H) mm ³ , 9.8 kg		485(L) ×381(W) ×133 (H) mm ³ , 12.4kg	