

MLL-III-1310 /1~20mW

LOW NOISE INFRARED DIODE LASER AT 1310nm





Low noise infrared diode laser at 1310nm is made features of round spot, long lifetime, low cost and easy operating, which is widely used in measurement, spectrum analysis, etc.



SPECIFICATIONS

Wavelength (nm)	1310 ± 10		
Output power (mW)	>1, 5, 10,....., 20		
Spectral line width (nm)	<0.3		
Noise of amplitude(rms,1~20MHz)	<1%		
Transverse mode	Near TEM ₀₀		
Operating mode	CW		
Power stability (rms, over 4 hours)	<1%, <3%, <5%		
Warm-up time (minutes)	<5		
Beam divergence, full angle (mrad)	<1.0		
Dimensions of beam at the aperture (mm)	~3.0		
Beam height from base plate (mm)	24.8		
Operating temperature (°C)	10~35		
Power supply (90-264VAC)	PSU-III-LED	PSU-III-FDA	PSU-III-OEM
Expected lifetime (hours)	10000		
Warranty	1 year		



MxL-III-1310	PSU-III-LED	PSU-III-FDA	PSU-III-OEM
 <p>139(L)×73(W)×46.2(H) mm³, 0.6kg</p>	 <p>153 (L) ×155(W) ×92 (H) mm³, 1.5kg</p>	 <p>133 (L) ×130(W) ×65 (H) mm³, 1.2kg</p>	 <p>100 (L) ×62(W) ×56 (H) mm³, 0.2kg</p>
