

MLL-III-445/1~1000mW

LOW NOISE BLUE DIODE LASER AT 445 nm

Low noise blue diode laser module at 445 nm is made features of ultra compact, long lifetime, low cost and easy operating, which is widely used industry and scientific research.



SPECIFICATIONS

Wavelength (nm)	445±5	
Output power (mW)	>1, 10, 20, ...,500	>500, 600, ...,1000
Transverse mode	Near TEM ₀₀	
Operating mode	CW	
Power stability (rms, over 4 hours)	<1%, <3%, <5%	
Noise of amplitude (rms, 1~20MHz)	<1%	
Warm-up time (minutes)	<5	
Beam divergence, full angle (mrad)	<1.5	<3.0×0.5
Dimensions of beam at the aperture (mm)	~5	~2×4
Beam height from base plate (mm)	24.8	
Pointing stability after warm-up (mrad)	<0.05	
Operating temperature (°C)	10~35	
Power supply (90-264VAC)	PSU-III-LED	PSU-III-FDA
Expected lifetime (hours)	10000	
Warranty period	1 year	



MxL-III-445	PSU-III-LED	PSU-III-FDA
 <p>139(L)×73(W)×46.2(H) mm³, 0.6kg</p>	 <p>153 (L) ×155(W) ×92 (H) mm³, 1.5kg</p>	 <p>133 (L) ×130(W) ×65 (H) mm³, 1.2kg</p>
		