

MPL-H-355/0.1~7uJ/1~50mW

LD PUMPED ALL-SOLID-STATE UV LASER




All solid state 355 nm UV laser is made features of ultra compact, long lifetime, low cost and easy operating, which is widely used in UV curing, micro-electronics, CD carving, laser medical treatment, scientific experiment, etc.



SPECIFICATIONS

Wavelength (nm)	355±1
Output average power (mW)	1~50
Transverse mode	Near TEM ₀₀
Operating mode	Q-switched pulsed laser
Single pulse energy (μJ)	0.1~7
Pulse duration (ns)	1.3
Peak power(kW)	~5
Rep. rate(kHz) Uncontrollable	Undefined rep. rate among 4k-7kHz and unstable laser pulse emitting.
Average power (mW)	Average power (mW) = Single pulse energy (μJ) * Rep. rate (kHz)
Ave power stability (over 4 hours)	<5%, <10%
Beam divergence, full angle (mrad)	<1.5
Beam diameter at the aperture (mm)	~2.0
Polarization ratio	>100:1
Pointing stability after warm-up (mrad)	<0.05
Warm-up time(minutes)	<10
Beam height from base plate (mm)	45
Operating temperature (°C)	10~35
Spectral purity	>99%
Power supply (90-264VAC)	PSU-H-FDA
Expected lifetime (hours)	5000
Warranty period	1 year
Remarks	Please Note: because of the Walk-off effect of Nonlinear crystals, the beam quality of UV laser is not so good as that of 1064/532nm laser.



MxL-H-355		PSU-H-FDA	
 <p>153(L)×77(W) ×60(H) mm³, 0.9 kg</p>		 <p>238 (L) ×146(W) ×102 (H) mm³, 2.3 kg</p>	