

## **PDF DATA SHEET**

EFORCEAUSTRALIA PTY.LTD ACN:159 503 401

ENCRUPE TO DIRECT OR SCATTERED RADACION

CLASS IV LASER PRODUCT

**AO-Z-457** /1~33uJ/1~1000mW

## LD PUMPED ALL-SOLID-STATE **AOM Q-SWITCHED LASER**

All solid state AOM Q-switched laser at 457 nm has the features of high peak power, high repetition rate, and short pulse duration, which is widely used in marking, carving, measure, research and so on.











## SPECIFICATIONS

Wavelength (nm)	457±1
Operating mode	Q-switch: AOM (Acousto-Optic Modulation)
Output power(mW)	1~1000
Single pulse energy (µJ)	1~33
Pulse duration (ns)	~300@30kHz
Peak power (W)	~110
Rep. rate (kHz)	1~50, adjustable by external control
Ave power stability (over 4 hours)	<5%, <10%
Warm-up time (minutes)	<10
Beam divergence, full angle (mrad)	<2
Beam diameter at the aperture (mm)	~4.0
Beam height from base plate (mm)	96
Cooled method	Air cooled
Operating temperature (°C)	10~35
Power supply (220/110VAC)	PSU-AOM(3U)
Expected lifetime (hours)	10000
Warranty period	1 year

