

MLL-III-1085/1~1000mW

LOW NOISE INFRARED LASER AT 1085nm





All solid state low noise infrared laser at 1085 nm is made features of ultra compact, long lifetime, low cost and easy operating, which is used in scientific experiment, measurement, optical instrument, optical sensor, communication, spectrum analysis, etc.



SPECIFICATIONS

Wavelength (nm)	1085±2		
Output power (mW)	>1, 5, 10, 20, ... , 1000		
Transverse mode	TEM ₀₀		
Operating mode	CW		
Power stability (rms, over 4 hours)	<1%, <3%, <5%		
Noise of amplitude (rms, 20Hz~20MHz)	<1%		
Warm-up time (minutes)	<10		
M ² factor	<1.5		
Beam divergence, full angle (mrad)	<1.5		
Beam diameter at 1/e ² (mm)	~1.5		
Beam height from base plate (mm)	24.8		
Pointing stability after warm-up (mrad)	<0.05		
Operating temperature (°C)	10~35		
Power supply (90-264VAC or 5VDC)	PSU-III-LED	PSU-III-FDA	PSU-III-OEM
Expected lifetime (hours)	10000		
Warranty	1 year		



MxL-III-1085	PSU-III-LED	PSU-III-FDA	PSU-III-OEM
 <p>140.8(L)×73(W)×46.2(H) mm³, 0.6kg</p>	 <p>153 (L) ×155(W) ×92 (H) mm³, 1.5kg</p>	 <p>133 (L) ×130(W) ×65 (H) mm³, 1.2kg</p>	 <p>100 (L) ×62(W) ×56 (H) mm³, 0.2kg</p>
