

MLL-III-395/1~100mW

LOW NOISE VIOLET DIODE LASER AT 395 nm

Violet low noise diode laser module at 395nm is made features of ultra compact, long lifetime, low cost and easy operating, which is used in measurement, communication, spectrum analysis, etc.



SPECIFICATIONS

Wavelength (nm)	395±5	
Output power (mW)	>1, 2, 3, ..., 100	
Transverse mode	Near TEM ₀₀	
Operating mode	CW	
Power stability (rms, over 4 hours)	<1%, <3%, <5%	
Noise of amplitude (rms, 1~20MHz)	<1%	
Warm-up time (minutes)	<5	
Beam divergence, full angle (mrad)	0.5	
Beam diameter at the aperture (mm)	~4.0	
Beam height from base plate (mm)	24.8	
Pointing stability after warm-up (mrad)	<0.05	
Operating temperature (°C)	10~35	
Power supply (90-264VAC)	PSU-III-LED	PSU-III-FDA
Expected lifetime (hours)	10000	
Warranty period	1 year	



MxL-III-395	PSU-III-LED	PSU-III-FDA
 <p>139(L)×73(W)×46.2(H) mm³, 0.6kg</p>	 <p>153 (L) ×155(W) ×92 (H) mm³, 1.5kg</p>	 <p>133 (L) ×130(W) ×65 (H) mm³, 1.2kg</p>
		