

MRL-D-655/2000-2500mW

RED DIODE LASER AT 655nm






Diode red laser 655nm is made features of ultra compact, long lifetime, low cost and easy operating, which is widely used in measurement, spectrum analysis, laser lighting show, etc.



SPECIFICATIONS

Wavelength (nm)	655 ± 10		
Output power (mW)	>2000, 2100, ..., 2500		
Transverse mode	Near TE ₀₀		
Operating mode	CW		
Power stability (rms, over 4 hours)	<1%, <3%, <5%		
Warm-up time (minutes)	<5		
Polarization direction	Horizontal/Vertical	Horizontal +Vertical	
Beam divergence, full angle (mrad)	<4.0×3.0		
Beam diameter at the aperture (mm)	8×5	8×2	
Beam height from base plate (mm)	45		
Operating temperature (°C)	10-35		
Power supply (100-240VAC or 8VDC)	PSU-III-FDA	PSU-III-LED	PSU-D-OEM
Modulation option	TTL/Analog 1Hz-5KHz, 1Hz-10KHz, 1Hz-30KHz, and TTL on/off		
Expected lifetime (hours)	10000		
Warranty	1 year		



MRL-D-655	PSU-III-LED	PSU-III-FDA	PSU-D-OEM	Adapter
 180(L)×86(W)×65(H) mm ³ , 1.6 kg	 154 (L) ×155(W) ×95 (H) mm ³ , 1.5kg	 133 (L) ×130(W) ×65 (H) mm ³ , 1.2kg	 86(L)×47(W) ×52(H) mm ³ , 0.10 kg	 100-240VAC
