

OEM-F-532/1-3000mW
LD PUMPED ALL-SOLID-STATE OEM GREEN LASER

All solid state 532 nm OEM green laser is made features of high stability, ultra compact, long lifetime, low cost and easy operating. It's easy to be installed in customer's equipment.


SPECIFICATIONS

Wavelength (nm)	532±1								
Output power (mW)	>1, 5, 10, ..., 450	500, 550, ..., 1400	1500, ..., 2000	2100, ..., 3000					
Transverse mode	TEM ₀₀	Near TEM ₀₀							
Operating mode	CW								
Power stability (rms, over 4 hours) at 25°C	<1%, <3%, <5%								
Warm-up time (minutes)	<10								
M ² factor	<1.2	<1.2	<3.0	<3.0					
Beam divergence, full angle (mrad)	<1.2								
Beam diameter at the aperture (mm)	3-4								
Beam height from base plate (mm)	25								
Operating temperature (°C)	25±/-2								
Operating current of Diode (A)	0-2.5	0-5.5	0-5.5	0-8					
Operating voltage of Diode (V)	~2.0								
Pins information	11/12: positive of diode; 1/2: negative of diode	5/6/7/8: positive of diode; 12/13/14/15: negative of diode							
Power supply (optional)	PSU-III-OEM (5VDC)	PSU-OEM-F (two channels 6 & 12V)							
TTL modulation/ Analog modulation	TTL on/off, 1Hz-1KHz, 1KHz-10KHz, 10KHz-30KHz; and Analog modulation option								
Expected lifetime (hours)	5000								
Warranty time	The warranty is 3 months, excluding the LD failure.								

Note: The power supply needs to be with the over current protection function.



OEM-F-532	F-532-HS	PSU-III-OEM (1-450mW)	Accessories	PSU-OEM-F(1-3000mW)	Accessories
136(L)×58(W)×45(H) mm ³ , 0.74kg	163(L)×77(W)×65(H) mm ³	100 (L)×62(W)×56 (H) mm ³ , 0.2kg		100(L)×76(W)×27(H) mm ³ , 0.10 kg	160(L)×86.2(W)×34.5(H) mm ³ 100-240VAC Adap